



1 PREPARE 2 TREAT 3 MAINTAIN

MASTER COLOUR OIL

APPLICATION AREA

Master Colour Oil provides colour and protection in one product. Perfect for indoor use on all unfinished, new or newly-sanded surfaces in all wood species.

RESULT

Master Colour Oil penetrates the wood and ensures a hardwearing surface with high resistance to dirt and fluids. Gives the wood a beautiful, breathable surface.



High resistance

Penetrates deep into the wood. High resistant to dirt and fluids, e.g. water, coffee, tea and red wine.



Natural solution

Isocyanate free and assures a minimum of waste. Gives the wood a beautiful breathable surface.



Easy to maintain

No special tools required. Just use the standard WOCA system.

Extra Grey

Antique

Walnut

Castle Grey

Rhode Island Brown

Brazil Brown

Light Brown

Black

White

Extra White

Natural



Product information

Coverage: 10-12 m²/L

Packaging: 1 L, 2.5 L & 5 L

Available in 11 colours



HOW TO...

...DO THE BASIC TREATMENT OF WOODEN FLOORS

Tools

- Either polishing machine or doodlebug for the manual finishing
- Paint roller and cotton cloths
- Clean tools with Solvent

Preparation

The wood must be newly sanded, use grit 100-120 for the final sanding. Vacuum thoroughly. Clean the wood with WOCA Intensive Wood Cleaner and leave it to dry for at least 8 hours before applying the oil.

Product, room and floor temperature must be between 15-30°C. Wood humidity must not exceed 12%. Ensure good ventilation during application and when drying.

Risk of self-ignition!





Due to the risk of self-ignition any cloths that have been soaked in oil should be stored/disposed of in sealed containers or incinerated.

Please note

Do not expose the surface to water or clean it for the first 7 days while the oil is hardening.

Maintenance and cleaning

For the cleaning, we recommend using WOCA Natural Soap or WOCA Oil Refreshing Soap. Re-oil the surface with WOCA Maintenance Oil or Maintenance Gel.



INSTRUCTIONS

- 1 Thoroughly shake the container of Master Colour Oil, both before and during use. Containers with different batch numbers should be mixed to avoid colour mismatch. Apply the oil using a short-bristled paint roller (4-6 mm) in an even coat. Work in small areas of no more than 10 m² at a time.
- 2 Leave the oil to soak in for 10-20 min. If the oil soaks quickly into the wood, apply more oil.
- 3 Polish the oil into the wood until the surface appears saturated. Use a buffing machine with a beige pad for large areas and a polishing cloth/pad manually for small areas.
- 4 Remove excess oil with dry, lint-free cotton cloths or pads until the surface no longer appears wet.
- 5 To ensure a good saturation the surface should be re-polished with 1 dl Master Colour Oil per 10 m² within 6-12 hours after the first application.

The surface can be used with caution after 12-24 hours and is fully hardened after 5-7 days at 20°C.

Cleaning of tools: With WOCA Solvent or turpentine.