



1 PREPARE 2 TREAT 3 MAINTAIN

MASTER MULTI PRIMER

PRODUCT DESCRIPTION

Master Multi Primer is a solvent-based, fast-drying and easy-to-sand wood primer, which will seal the wood and improve the adhesion of a subsequent coat of lacquer. The primer is especially suitable as a problem-solving primer on old and previously treated floors, as well as a primer for exotic, oily wood varieties.

APPLICATION AREA

For exotic wood varieties and old and previously treated wooden floors.



30-60 min

Quick-drying

Before application of lacquer: 30-60 min.



Side-bondings

Minimizes side-bondings

Reduces the risk of side-bondings due to a high flexibility.



surface

Solvent-based

Especially suited for troublesome wooden floors. Improves adhesion of lacquer.



Product information

Coverage: 10-12 m²/L

Packaging: 5 L



WORK DESCRIPTION

Preparation

It is important that both wood and primer have a temperature of min. 15°C (preferably around 20°C) and air humidity of approx. 50%. Make sure that the room is well-ventilated for optimal evaporation and drying time.

For the final sanding to bare wood, use grit 100-150 sandpaper or sanding pad. Vacuum thoroughly and wipe the floor down afterwards if necessary, using a tightly-wrung water-soaked cloth. The floor must be completely dry before Master Multi Primer is applied.

Note

Master Multi Primer is ready for use and should not be diluted. It may be necessary to apply an extra coat of Master Multi Primer on surfaces made of exotic wood or fruitwood.



TREATMENT

- 1 Shake the container well before use.
- 2 Apply undiluted Master Multi Primer with a short-bristle roller (6 mm), using light movements lengthways along the wood.
- 3 Leave the wood primer to dry for 30-60 minutes.
- 4 The floor can then be finished with one of WOCA's lacquers, following the instructions for the lacquer you have chosen. This product is not suitable for use with WOCA Invisible 2K Lacquer.